

FSK93847P





World's first lift-and-load. Bring the dishes to you

The 9000 ComfortLift® Dishwasher revolutionises dishwashing with the world's first lift-and-load basket. This advanced mechanism lifts the rack to a comfortable height for easy loading and unloading.

Product Benefits & Features



Lifts gentle to a new level

This world-leading ComfortLift® gently lifts the lower dishwasher rack up to a comfortable height. For easy loading and unloading. Elevating dishwashing to a whole new level.

- · Capacity: 14 place settings
- Sensorlogic
- 4 temperature settings
- 7 programmes including:
- Auto half load
- Multi-tab
- · Delay start of up to 24 hours
- Time remaining indicator
- Height adjustable upper basket
- Foldable plate rack



Always gentle on dishes

With ComfortRails, you can smoothly slide the basket into place without any rattle of the plates. Always smooth to load and unload. You never have to worry about any chips or cracks in your dishes.

The uncomplicated way to responsible dishwashing

Responsible choices made easy. Use the QuickSelect touchscreen slider to select your prefered cycle time and the Ecometer guides you to the most sustainable program to save energy and water through visually green bars.

More Visibility, More Efficient Loading

Instantly see the racks and configurations in your dishwasher courtesy of the interior light. With increased visibility, you can see where best to place your items more efficiently and effortlessly, meaning you can load everything away in one seamless process.

Always know exactly when the dishwasher is done

Thanks to TimeBeam you can be fully up to date on the status of your dishwashing cycle at a glance. While the cycle is still in progress, TimeBeam technology projects the remaining amount of time in a clear red light on the floor. Simple, straightforward and effective.



FSK93847P

Product Specification		
Construction type	Built-In	Тор
Installation	Fully integrated	Anti-
Dimensions (mm) (HxWxD)	818x596x550	Opti
Built-under installation dimensions, mm (HxWxD)	820-900x600x550	Dryii
Double Hinges	Sliding	Dish
Water Supply	Cold or hot	
Cord Length (m)	1.6	Proc
Inlet hose length (cm)	180	Nois
Outlet hose length (mm)	180	Max (EU
Connected load (W)	1550-2200	Ene
Wheels/feet	2 adj feet + 1 front adj rear foot;Adj 0 to 8 cm	(EU) Wei
Voltage (V)	200-240	per
Required Fuse	10	prog
Cleaning performance index (EU 2017/1369)	1.121	The
Drying performance index (EU 2017/1369)	1.061	2017
Frequency (Hz)	50-60	
Number of programmes	7	
Number of Temperatures	4	
Door Colour	None	
Inlet Pipe Type	Aqua control	
Spray arm	Satellite spray arm	

Top spraing level	Ceiling spray arm
Anti-flood Device	Floating switch
Options	Extra Silent, GlassCare, XtraPower
Drying System	with AirDry Technology
Dishwasher programs	160 Minutes, 60 Minutes, 90 Minutes, AUTO Sense, ECO, Machine Care, Quick 30 Minutes
ProdPartCode	K - Customer Specific KRT
Noise Level	39
Maximum number of place settings (EU 2017/1369)	14
Energy Efficiency Class (Regulation (EU) 2017/1369)	D
Weighted energy consumption in kWh per 100 washing cycles of eco 40-60 programme (EU 2017/1369)	85
The water consumption of the eco programme in liters per cycle (EU 2017/1369)	11

